



# DOWNLIGHTS

## SINOPE COMPACT FLUORESCENT DOWNLIGHTS


The Sinope compact fluorescent range of downlights are available in nominal 200mm diameter models. There are two versions, either open or enclosed. The enclosed version is supplied with a flush mounted tempered glass rated to IP44. The Sinope utilises a specular reflector and is designed for lamps to be mounted in a horizontal position. The lamps are TC-DE type for all models. The 18w & 26w versions are available with either integral or remote electronic control gear. The 42w versions are only available with electronic gear in a remote box. They may be supplied for hard wiring or fitted with flex & plug.

### RECESSED MOUNTED

#### 200mm (8") Open Downlight

- SN218PL** 2/18w TC-D
  - SN226PL** 2/26w TC-D
  - \*SN242PL** 2/42w TC-D
- Cut out size Ø 210mm


*\*Remote gear box is required & supplied in separate carton*




#### 200mm (8") Flushed Glass Downlight (IP44 trim only)

- SN218PLG** 2/18w TC-D
  - SN226PLG** 2/26w TC-D
  - \*SN242PLG** 2/42w TC-D
- Cut out size Ø 210mm

*\*Remote gear box is required & supplied in separate carton*



#### *\*Remote Gear Box*



Conventional control gear: Lamps: TC-D, 13 watt G24d1 base  
18 watt G24d2 base. 26 watt G24d3 base  
Electronic control gear: TC-DE lamp, 13 watt G24q1 base  
18 watt G24q2 base. 26 watt G24q3 base