

SPECIAL APPLICATION

SEALED RECESSED PLASTER

The sealed recessed plaster range of luminaires are designed to prevent contaminants, such as dirt & insects, from building up or entering the environment via the luminaire. There are no areas on the body or lens panel where dirt particles can accumulate. To prevent contaminant build-up, the external side of the lens panel has a smooth surface & the body of the luminaire is constructed such that there are no horizontal surfaces where dirt can sit. A rubber gasket provides a good seal between the lens panel & the body of the luminaire to prevent contaminant entry to the environment via the luminaire. They are used extensively in the food industry in areas of preparation & display, and anywhere where a general dust free environment is essential.



ATLAS SERIES

The Atlas sealed plaster is a front access luminaire for recessed mounting and incorporates a 1mm thick lanyard retained diffuser frame. The diffuser consists of two layers. The bottom layer is a clear acrylic lens for easy cleaning. The top overlay is a prismatic acrylic diffuser.


RECESSED PLASTER T8

Atlas Sealed Plaster

For plaster recessed ceilings. x designates diffuser overlay type.

Y5, Y7, K12, K15, K19, K19T silver tint

ATPS218xC	2/18w	680mm
ATPS318xC	3/18w	680mm
	Cut out size 645 x 290	
ATPS236xC	2/36w	1290mm
ATPS336xC	3/36w	1290mm
	Cut out size 1245 x 290	



SPECIAL APPLICATION


RECESSED PLASTER T5



Atlas Sealed Plaster

For plaster recessed ceilings. x designates diffuser overlay type.

Y5, Y7, K12, K15, K19, K19T silver tint.



ATPS214T5xC	2/14w	680mm
ATPS314T5xC	3/14w	680mm
ATPS224T5xC	2/24w	680mm
ATPS324T5xC	3/24w	680mm

Cut out size 645 x 290

ATPS228T5xC	2/28w	1290mm
ATPS328T5xC	3/28w	1290mm
ATPS254T5xC	2/54w	1290mm
ATPS354T5xC	3/54w	1290mm

Cut out size 1245 x 290