

PHOEBE CT

Commercial Lighting / Batten

PBW220CT

Features

- Colour temperature selectable
- White powder coated mild steel body
- Opalised polycarbonate diffuser
- Quick and easy installation
- Suitable for surface or pendant mount

Applications

- Retail shops
- Kitchens, canteens
- Public amenities
- Corridor and entrance areas
- Covered carparks, workshops

Options

- Dimmable
- Sensor
- Emergency

Standards


Manufactured under ISO 9001:2015 to standards
IEC/AS/NZS 60598.1
IEC/AS/NZS 60598.2.1
IEC/AS/NZS CISPR 15

Mounting Methods



Surface mounted

Pendant



PHOEBE CT

Commercial Lighting / Batten


Specifications

Model	PBW220CT
Nominal Power (W)	20
Input Voltage (V)	220 - 240 VAC 50 / 60 Hz
Luminaire Flux (lm)	2120
Luminaire Efficacy (lm/W)	110
CRI (Ra)	> 80
Power Factor	> 0.90
CCT (K)	3000/4000/6500
Luminaire Rated Life (hr)	30000
Ambient Temp. ta (°C)	35
Weight (kg)	1.1

Packaging Details

Model	PBW220CT
Product Carton Qty per box (pc)	1
Product Carton Dimension (mm)	1177 X 70 X 79

Lighting Data



PHOEBE CT

Commercial Lighting / Batten

Dimensions

